

PCT


WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

EP 025 82 38

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁴ : A61M 15/00 // G06M 1/00	A1	(11) International Publication Number: WO 86/ 05991 (43) International Publication Date: 23 October 1986 (23.10.86)
(21) International Application Number: PCT/SE86/00164 (22) International Filing Date: 9 April 1986 (09.04.86) (31) Priority Application Number: 8501806-7 (32) Priority Date: 12 April 1985 (12.04.85) (33) Priority Country: SE (71) Applicant: AKTIEBOLAGET DRACO [SE/SE]; Box 34, S-221 00 Lund (SE). (72) Inventor: VIRTANEN, Risto ; Torenvägen 14C, SF-01900 Nurmijärvi (FI). (74) Agents: HJERTMAN, Ivan, T. et al.; AB Astra, Patent and Trademark Department, S-151 85 Södertälje (SE).	(81) Designated States: AT, AT (European patent), AU, BB, BE (European patent), BG, BR, CF (OAPI patent), CG (OAPI patent), CH, CH (European patent), CM (OAPI patent), DE, DE (Utility model), DE (European patent), DK, FI, FR (European patent), GA (OAPI patent), GB, GB (European patent), HU, IT (European patent), JP, KP, KR, LK, LU, LU (European patent), MC, MG, ML (OAPI patent), MR (OAPI patent), MW, NL, NL (European patent), NO, RO, SD, SE, SE (European patent), SN (OAPI patent), SU, TD (OAPI patent), TG (OAPI patent). Published With international search report.	

(54) Title: AN INDICATING MEANS FOR A DOSAGE DISPENSING DEVICE



(57) Abstract

An indicating means in a dosage dispensing device for medicaments, particularly a dosage inhaler which indicates a number of dosages administered from the dosage dispensing device. The indicating means includes a rotatable disc (1) having apertures (2) passing therethrough which can be filled with a medicament in particle form. By rotating the disc the apertures can be brought into an air channel or duct (3) through which air is inhaled. The rotatable disc has associated with a central portion a spiral groove or ridge (4) which can engage with peripheral teeth (8) on a toothed wheel (6), such that rotation of the disc (1) results in rotation of the toothed wheel and the toothed wheel is provided with one or more markings (9) which are visible from outside the dosage inhaler upon rotating the disc a predetermined number of times.

BEST AVAILABLE COPY

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT Austria
AU Australia
BB Barbados
BE Belgium
BG Bulgaria
BR Brazil
CF Central African Republic
CG Congo
CH Switzerland
CM Cameroon
DE Germany, Federal Republic of
DK Denmark
FI Finland
FR France

GA Gabon
GB United Kingdom
HU Hungary
IT Italy
JP Japan
KP Democratic People's Republic
of Korea
KR Republic of Korea
LI Liechtenstein
LK Sri Lanka
LU Luxembourg
MC Monaco
MG Madagascar
ML Mali

MR Mauritania
MW Malawi
NL Netherlands
NO Norway
RO Romania
SD Sudan
SE Sweden
SN Senegal
SU Soviet Union
TD Chad
TG Togo
US United States of America

AN INDICATING MEANS FOR A DOSAGE DISPENSING DEVICETechnical Field

The present invention relates to an indicating means for a dosage dispensing device for medicaments, and in particular to an indicating means for a dosage inhaler, effective to indicate a number of medicament dosages administered. A dosage dispensing device, and in particular a dosage inhaler, provided with indicating means constitutes a further aspect of the invention.

One object of the invention is to provide an indicating means which will clearly indicate to the user a given number of dosages administered, and primarily a number at which the store of medicament in the dosage dispensing device is exhausted. A further object is to provide an indicating means which can be used to indicate small quantities of medicament which are difficult to discern by direct observation.

Background Prior Art

Inhalers intended for medicaments in powder form are known to the art. EP 0069715 describes and illustrates one such device in which the powder is metered in given dosages through apertures located in a rotatable disc, these apertures being introduced into an airduct or channel through which air is inhaled, by rotating the disc. A characteristic feature of this type of inhaler is that it is used to administer a precise amount, or dosage, of highly potent medicaments, which are consequently metered in extremely small amounts, for example 0.1 mg. The stored amount of medicament is also kept small, for example 10-30 mg. Such a small quantity, and the change therein, cannot readily be discerned by direct observation. In this case there is a risk of the supply of medicament becoming exhausted without the patient noticing the fact in time, which results in the patient missing his/her treatment with the subsequent risk to the wellbeing of the patient.

-2-

Consequently, there is a need for an indicator which will readily indicate a number of dosages administered in a clear and unambiguous fashion.

5 The need for indicating the number of dosages measured in the aforesaid minute quantities of medicinal substances is also found in dosage dispensing devices other than dosage inhalers.

Brief Description of the Invention

10 The present invention starts from the concept of an indicating means for a dosage dispensing device for medicaments, particularly for a dosage inhaler, in which the means comprise a rotatable disc provided with apertures passing therethrough which can be filled with a medicament
15 in particle form and which, by rotating the disc, can be placed in register with an airduct or channel through which air is inhaled.

The invention of the present Application resides in the fact that the rotatable disc has associated with the
20 central portion thereof a spiral groove or ridge which is engageable by teeth located on the periphery of a toothed wheel and extending transverse to the spiral groove or ridge, such that rotation of the disc results in rotation of the toothed wheel and in that the toothed wheel is
25 provided with one or more markings which are visible from outside the dosage inhaler upon rotation of the disc a predetermined number of times.

The toothed wheel may be positioned at any angle to the disc, with the teeth extending transverse to the
30 spiral groove or ridge on the rotatable disc, however. The toothed wheel preferably extends in a diametral plane of disc with the spiral groove or ridge arranged to draw the teeth of the toothed wheel in towards the center of the disc when the disc is rotated in its intended direction of
35 rotation. To this end, the spiral groove or ridge is

-3-

preferably so arranged that its outermost part is located at a shorter radial distance from the center of the disc than the projection of the axis of the shaft of the toothed wheel on the disc. Advantageously a latching means is
5 arranged for resilient engagement between the teeth of the toothed wheel to prevent the wheel from rotating other than when caused to rotate by rotation of the disc.

The marking or markings which can indicate a number of dosages corresponding, for example, to a
10 substantially all or half of the quantity of medicaments stored in a device, or to a number of dosages prescribed for a given period of time are, in accordance with the preferred embodiment of the invention, arranged so that each marking is visible in a window provided in the
15 outer wall of the dosage inhaler.

The invention also provides a dosage inhaler incorporating the indicating means of the invention, together with a medicament storage space and an air duct through which air is inhaled, the apertures in the
20 rotatable disc being capable of being brought into register with the air duct.

The invention will now be described in more detail with reference to an embodiment thereof illustrated in the accompanying drawings, in which
25 Figure 1 is a side elevation in section of the upper part of one embodiment of dosage inhaler incorporating indicating means according to the present invention;
Figure 2 is a perspective of the internal components of
30 the dosage inhaler shown in Figure 1;
Figure 3 is an exploded perspective view of the components shown in Figure 2;
Figure 4 illustrates in perspective the external configuration of a dosage inhaler according to
35 the invention provided with a mouthpiece; and

-4-

Figure 5 illustrates in perspective the external configuration of the dosage inhaler according to the invention in the absence of a mouthpiece.

In the drawings, a rotatable disc 1 forms part of a dosage inhaler and has located on the surface thereof a number of groups of apertures 2 which pass through the disc. In one rotational position of the disc, a group of apertures can be filled with medicament in particle form and then be rotated to a position in which they lie in register with an airduct 3 through which the medicament can be inhaled. An indicating means is provided by a spiral groove or ridge 4 mounted on the end of a central shaft 5 connected to the disc 1, and a toothed wheel 6 is mounted above and in a diametral plane of the disc 1, and rotatable about an axis perpendicular to the axis of the disc, on a shaft 7 journaled in the dosage inhaler. The toothed wheel 6 has arranged around its periphery a plurality of radially projecting teeth 8, of which at least one engages the spiral groove or ridge 4 in a manner such that rotation of the disc 1 results in rotation of the toothed wheel 6. Located on the periphery of the toothed wheel is a colour marking 9, which can be brought into view in a window 10 provided in the outer wall of the dosage inhaler, by rotating the toothed wheel.

The disc 1 is provided with ratchet teeth 11, by means of which the disc can be rotated in the desired direction. The spiral groove or ridge 4 is so arranged that upon rotation of the disc in this desired direction that tooth, or those teeth, of the toothed wheel 6 engaging the spiral groove or ridge 4 is, or are, drawn towards the center of the disc 1. The toothed wheel is so positioned that the projection of the axis of the shaft 7 on the disc lies at a greater radial distance from the center of the disc than the outer most part of the spiral groove or ridge 4. Arranged above the toothed wheel 6 is a latching means

12 in the form of a latching pawl arranged to engage between the teeth of the toothed wheel.

In addition to the aforescribed indicating means according to the invention, the inhaler also
5 incorporates known components necessary for its function, such as a medicament storage compartment 13 and an associated filling channel 14. A mouthpiece 15 encloses the upper part of the inhaler and has a form which enables it to be placed in the mouth of a patient. The rotatable
10 disc 6 is indexed by operating means 16 known per se having a pawl or the like engageable with ratchet teeth 11.

-6-

CLAIMS

1. An indicating means for a dosage dispensing device for medicaments, particularly a dosage inhaler, said means comprising a rotatable disc (1) provided with apertures (2) passing therethrough, which can be filled
5 with a medicament in particle form and which, by rotation of the disc, can be placed in register with an airduct or channel (3) through which the air is inhaled, characterised in that the rotatable disc has associated with the central portion a spiral groove or ridge (4) which is engageable
10 by teeth (8) located in the periphery of the toothed wheel (6) and extending transverse to the spiral groove or ridge (4), such the rotation of the disc (1) results in rotation of the toothed wheel (6); and in that the toothed wheel is provided with one or more markings (9) which are visible
15 from outside the dosage inhaler upon rotation of the disc a predetermined number of times.

2. An indicating means according to claim 1, characterised in that the toothed wheel (6) extends in a diametral plane of the disc and in that the spiral groove
20 or ridge (4) is arranged to draw the teeth (8) of the toothed wheel in towards the center of the disc when the disc is rotated in its intended direction of rotation.

3. An indicating means according to claim 2, characterised in that the outermost part of the spiral groove or ridge (4) is located at a shorter radial distance
25 from the center of the disc (1) than the projection of the axis of the shaft (7) of the toothed wheel on the disc.

4. An indicating means according to one or more of the preceding claims, characterised in that a latching
30 means (12) is arranged for resilient engagement between the teeth of the toothed wheel.

5. An indicating means according to one or more of the preceding claims, characterised in that each marking
35 is arranged to be brought into view in a window (10) provided in the outer wall of the dosage inhaler.

6. A dosage inhaler comprising an indicating means according to one or more of the preceding claims, and further comprising a medicament storage space (13) and an air duct (3) through which air is inhaled, the apertures in
5 the rotatable disc (1) being capable of being brought into register with the air duct.




FIG. 1






FIG. 2

FIG. 3



2/2




FIG. 4




FIG. 5

INTERNATIONAL SEARCH REPORT

International Application No

PCT/SE86/00164

I. CLASSIFICATION OF SUBJECT MATTER (if several classification symbols apply, indicate all) *

According to International Patent Classification (IPC) or to both National Classification and IPC₄

A 61 M 15/00 // G 06 M 1/00

II. FIELDS SEARCHED

Minimum Documentation Searched ⁷

Classification System	Classification Symbols
IPC 3,4 US C1	A 61 M 11/00-/08, 13/00, 15/00-/08 128:185, 213, 260, 265-266; 235:1, 67, 103, 107, 133, 134; 604:58, 99

Documentation Searched other than Minimum Documentation
to the Extent that such Documents are Included in the Fields Searched *

SE, NO, DK, FI classes as above

III. DOCUMENTS CONSIDERED TO BE RELEVANT *

Category *	Citation of Document, ¹¹ with indication, where appropriate, of the relevant passages ¹²	Relevant to Claim No. ¹³
A	NO, B, 146 343 (A.C.G POORE) 7 June 1982	1, 5, 6
A	US, A, 786 073 (S.P. WALSH) 28 March 1905	1
A	US, A, 4 034 757 (F.G. GLOVER) 12 July 1977	1, 6

* Special categories of cited documents: ¹⁰

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

IV. CERTIFICATION

Date of the Actual Completion of the International Search

1986-07-07

Date of Mailing of this International Search Report

1986-07-14

International Searching Authority

Swedish Patent Office

Signature of Authorized Officer

Leif Karnsäter
Leif Karnsäter

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☒ FADED TEXT OR DRAWING
- ☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☐ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.